

Gull Wing®

Portable Power Distribution Systems

GW Series Portable Units 200 thru 400 Amps

- ➔ Available in Single or Three Phase
- ➔ Powder Coat Painted for Ultimate in Durability
- ➔ Intel-A-Lite Ground and Continuity Monitor
- ➔ Choose From Standard or Custom Models
- ➔ UL Listed Models Meet or Exceed NEC Requirements
- ➔ Nema 3R Rainproof Construction with Cords Connected
- ➔ All Copper Buss Bar
- ➔ One Year Warranty
- ➔ Square D Circuit Breaker
- ➔ Stainless Steel Exterior Hinges
- ➔ Lockable Lids for Security and Safety

Line Side Options

- ➔ Hardwired
- ➔ Advanced Devices CL
- ➔ Crouse Hinds Cam Lok
- ➔ Leviton ECT
- ➔ Abbott Safety Lock
- ➔ Meltric Receptacles
- ➔ IEC 309 Pin & Sleeves
- ➔ Fused Feed Thrus
- ➔ Up to 3 Nonfused Feed Thrus

This symbol on the nameplate means the product is listed by the Underwriters Laboratories Inc.



Load Side Options

- ➔ Meltric Receptacles
- ➔ Advanced Devices CL
- ➔ Crouse Hinds Cam-Lok
- ➔ Leviton ECT
- ➔ Spec Grade Locking Receptacles
- ➔ Heavy Duty Straight Blade Receptacles
- ➔ IEC 309 Pin & Sleeves

Power Distribution Systems for the Amusement Industry

Gull Wing Industries, Inc.

P.O. Box 128, 309 NE 1st Street, Alta, Iowa 51002

www.gull-wing.com

800-838-1482

Fax 712-200-1936

712-200-2747

Two Popular Models from the GW Series

This 200 amp unit is a **GW200 Model** with a hardwired line side and the following load side:

- 1-Nema 5-20, 20 amp, 120v, GFCI duplex receptacle
- 2-Nema 14-50, 50 amp, 120/240v, 4 wire, straight blade receptacle
- 4-Nema L14-30, 30 amp, 120/240v, 4 wire, locking receptacle
- 5-Nema L5-30, 30 amp, 120v, locking receptacle
- 1-Nema L21-30, 30 amp, 120/208v, 3 phase 5 wire, locking receptacle
- 2-Meltric, 60 amp, 120/208v, 3 phase 5 wire, load break receptacle
- 1-Meltric, 100 amp, 120/208v, 3 phase 5 wire, load break receptacle



This 400 amp unit is a **GW400 Model** with one 400 amp E1016 Major Cam-Lok input and two 400 amp Major Cam-Lok feed thrus (non-fused) and the following load side:

- 1-Nema 5-20, 20 amp, 120v, GFCI duplex receptacle
- 4-Nema L14-30, 30 amp, 120/240v, 4 wire, locking receptacle
- 5-Nema L5-30, 30 amp, 120v, locking receptacle
- 1-Nema L21-30, 30 amp, 120/208v, 3 phase 5 wire, locking receptacle
- 2-Nema 14-60, 60 amp, 120/240v, 4 wire, straight blade receptacle
- 2-60 amp, E1015 mini Cam-Lok J series, 120/208v, 3 phase 5 wire
- 1-100 amp, E1015 mini Cam-Lok J series, 120/280v, 3 phase 5 wire

